









Engine Specifications












GV 500

| Rating 50 Hz (1500 RPM) | KVA | KW |
|----------------------------|-----|-----|
| Continuous (C) | | |
| Prime (P) | 500 | 400 |
| Standby (S) | 550 | 440 |

LUBRICATING SYSTEM Wet Oil Dipstick Full-Flow Oil Filter Of Spin-On By-Pass Oil Filter Of Spin-On Type Oil Cooler, Side Mounted Low Noise Oil Sump





| FUEL SYSTEM | |
|----------------------------|------------------|
| Mechanical Fuel Filters Of | |
| Disposable Type | |
| Electronic Unit Injectors | |
| Pre-Filter with Water | |
| Separator | |
| | 198 g/kwh @ 100% |
| Fuel Consumption | Prime Power |
| | 198 g/kWh @ 100% |
| | Standby Power |

| ELECTRICAL EQUIPMENT | |
|----------------------|--------------|
| Altenator | 80A / 24 V |
| Starter motor | 7.0kw , 24 V |

SAFETY DEVICE

Low Oil Pressure High Water Temperature and Overspeed







GV 500

Weight & Dimensions

| DIMENSION | | OPEN | SILENT |
|-----------|----|------|--------|
| Length | mm | 3250 | 4350 |
| Width | mm | 1230 | 1600 |
| Height | mm | 1800 | 2250 |
| Weight | Kg | 3878 | 5122 |

L







