







Engine Specifications

DIESEL ENGINE DATA	HĒ
Engine Model	VOLVO TAD1642GE
No Of Cylinder / Arrangement	6 , in Line
Cycle	4 Stroke
Aspiration	Turbocharged
Bore X Stroke	144 X 165 mm
Displacement Total	16.12 liters
Compression Ratio	16.5:1
Combustion System	Direct Injection
Direction Of Rotation	Anti Clockwise Viewed On Flywheel
Cooling System	Tropical Radiator Incl Intercooler
Air intake system	Mounted Air Filter









GV 570

Rating 50 Hz (1500 RPM)	KVA	KW
Continuous (C)		
Prime (P)	570	456
Standby (S)	627	501

LUBRICATING SYSTEM	
Oil Dipstick	
Full-Flow Oil Filter Of Spin-On Type	
By-Pass Oil Filter Of Spin-On Type	
Oil Cooler, Side Mounted	
Low Noise Oil Sump	
Total Lubrication Capacity	48 Liters



FUEL SYSTEM Fuel Filters Of Disposable Type Electronic Unit Injectors Pre-Filter with Water Separator Fuel Consumption 200 g/kwh @ 100% Prime Power 202 g/kWh @ 100% Standby Power

ELECTRICAL EQUIPMENT	®
Altenator	60A / 24 V
Starter motor	7.0kw , 24 V

SAFETY DEVICE

Low Oil Pressure High Water Temperature and Overspeed







GV 570

Weight & Dimensions

DIMENSION		OPEN	SILENT
Length	mm	3250	5000
Width	mm	1250	1600
Height	mm	2550	2250
Weight	Kg	3878	5122

L







