







Engine Specifications

DIESEL ENGINE DATA	HØI
Engine Model	VOLVO TWD1644GE
No Of Cylinder / Arrangement	6 , in Line
Cycle	4 Stroke
Aspiration	2 Stage Turbocharged With Intercooling and Aftercooling
Bore X Stroke	144 X 165 mm
Displacement Total	16.12 liters
Compression Ratio	16.8:1
Combustion System	Direct Injection
Direction Of Rotation	Anti Clockwise Viewed On Flywheel
Cooling System	Water Cooled
Air intake system	Mounted Air Filter

GENERATOR DATA		- ■
Manufacture	REXFORD	
Phase Power	3	
Voltage	230/400 Volt	
Power Factor	0.8	
Coupling	Direct	
Bearing Number	1	
Index Protection	22	
Insulation Class	Н	
Exciter Type	S Hunt	
Pole Number	4	







GV 650

Rating 50 Hz (1500 RPM)	KVA	KW
Continuous (C)		
Prime (P)	652	521
Standby (S)	717	573

LUBRICATING SYSTEM	
Full Flow Oil Cooler	
Full Flow Disposable Spin On Oil Filter	
Bypass Filter With Extra High Filtration	
Total Lubrication Capacity	48 Liters

COOLING SYSTEM	
Dual Circuit	
Belt Driven Coolant Pumps	
With High Degree Of	
Efficiency	
Water Cooled Charge Air	
Coolers	
Total Coolant Capacity Incl.	50 Liters
Piping, CAC Circuit, KT	30 Litters

Piping, CAC circuit, Ki	
FUEL SYSTEM	
Electronic High Pressure Unit Injectors	
Fuel Prefilter With Water Sparator and Water in Fuel Indicator / Alaram	
Fine Fuel Filter With Manual Feed Pump And Fuel Pressure Sensor	
Fuel Consumption	194 g/kwh @ 100% Prime Power 192 g/kWh @ 100% Standby Power

ELECTRICAL EQUIPMENT	®
Altenator	80A / 24 V
Starter motor	7.0kw , 24 V
SAFETY DEVICE	\triangle
Low Oil Pressure	
High Water Temperature and Overspeed	









Weight & Dimensions

DIMENSION		OPEN	SILENT
Length	mm	3260	5250
Width	mm	1330	1800
Height	mm	2816	2300
Weight	Kg	4750	7400

L







